

LED Street Light



Sl.No.	Model No.	Power (Watt)	Lumen(LM)	CRI.	Color Temp (CCT).	Beam Angle	N.W(KG)	Materials	Power Factor (PF)	Dimension mm	LED Type
01	EL-ASRT-50	50W	65,00lm	>70Ra	3000K to 6000K	120°	4.0	Al+PC	>0.9	577x233x103	2835
02	EL-ASRT-100	100W	13,000lm	>70Ra	3000K to 6000K	120°	5.0	Al+PC	>0.9	627x272x103	2835
03	EL-ASRT-150	150W	19,500lm	>70Ra	3000K to 6000K	120°	5.0	Al+PC	>0.9	627x272x103	2835
04	EL-ASRT-200	200W	260,00lm	>70Ra	3000K to 6000K	120°	6.5	Al+PC	>0.9	767x300x103	2835

Features:

- Highly energy efficient - up to 130 lm/w
- Tool Free Access to Driver Box.
- Rugged One-piece Die Cast Housing.
- Easy Installation, Direct Slide-in Mount.
- Multiple Choice of Optical Lenses.
- IP65 rated for all outdoor conditions
- 5 Years warranty
- Operating Temperature-30 to 55°C (-22 to 131°F)
- Storing Temperature-40 to 80°C (-40 to 176°F)

