

# LED Flood Light



Sl.No.	Model No.	Power(Watt)	Efficacy	Total Lumen	Net Weight	Dimension
01	EL-PEDARL-50FL	50 W	180LPW	9,000lm	5.4kg/11.9lbs	352x370x175 mm 13.9x14.6x6.9 in
02	EL-NEDARL-100FL	100 W	180LPW	18,000lm	6.5kg/14.3lbs	446x370x175 mm 17.6x14.6x6.9 in
03	EL-NEDARL-150FL	150 W	180LPW	27,000lm	7.5kg/16.5lbs	540x370x175 mm 21.3x14.6x6.9 in
04	EL-NEDARL-200FL	200 W	180LPW	36,000lm	7.9kg/17.4lbs	619x410x180mm 24.4x16.1x7.1 in
05	EL-NEDARL-300FL	300 W	180LPW	54,000lm	14.8kg/32.6lbs	807x410x175 mm 31.8x16.1x6.9 in
06	EL-NEDARL-450FL	450 W	180LPW	81,000lm	18.3kg/40.3lbs	1098x420x180 mm 43.2x16.5x7.1 in

## Features:

- Ultra Bright, Up to 192,000lm
- Lumen Maintenance: 170>100,000 Hours (Calculated Using TM-21Calculator)
- Flexible, Modular design & Multiple Choice of Optical Lenses & easy Installation & Maintenance
- Input Voltage 100-277 VAC (347/480 VAC Optional) Dimming Optional
- IP66 & IK08 rated for all outdoor conditions
- Operating Temperature; -30 to 50°C (-22 to 131° F)
- Storing Temperature: -40 to 80°C (-40 to 176° F)
- Color Temperature 4500-5500K & 2500-5500K (Optional)
- LED Chip make : Philips Lumileds / Cree

