

LED High Bay Light



Sl.No.	Model No.	Power (Watt)	Lumen(LM)	CRI.	Color Temp (CCT).	Beam Angle	N.W(KG)	Materials	Power Factor (PF)	Dimention mm	LED Type
01	E-VARAEX-20	20W	28,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	4.15	Al+glass	>0.95	36.5x27x30.5	2835
02	E-VARAEX-40	40W	56,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	4.15	Al+glass	>0.95	36.5x27x30.5	2835
03	E-VARAEX-60	60W	84,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	6.95	Al+glass	>0.95	37.5x34x21.5	2835
04	E-VARAEX-80	80W	112,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	6.95	Al+glass	>0.95	37.5x34x21.5	2835
05	E-VARAEX-100	100W	140,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	6.95	Al+glass	>0.95	37.5x34x21.5	2835
06	E-VARAEX-120	120W	168,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	8.3	Al+glass	>0.95	48.5x34x36.5	2835
07	E-VARAEX-180	180W	210,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	8.3	Al+glass	>0.95	48.5x34x36.5	2835
08	E-VARAEX-200	200W	280,00lm	>70Ra	2700K to 7000K	40°/60°/90°/120°	8.3	Al+glass	>0.95	48.5x34x36.5	2835

Features:

- High quality SMT LED and Meanwell Driver.
- Light-weight design by aircraft aluminum.
- Heavy-duty and high impact resistance.
- Three connection cable entry points.
- Replaceable LED board and drivers.
- Integrated junction box for driver.
- Dimmable and battery back up function available.

- Marine rating powder coated appearance treatment.
- Two types of size available.
- High energy efficiency.
- Voltage range: 100-277/200-480V
- Protection rating: IP66 & IK10
- 10kv surge protection.
- Up to ten years limited warranty option.
- Emergency Battery back up(Optional).
- Working temperature can be more than 85°C.

- Various installation ways for different applications.
- Polycarbonate lens to make wider beam angle.
- Customized motion sensor(Optional).
- Advanced smart system: WIFI & BLUE-TOOTH(Optional).
- Warranty 5 years