

LED High Mast Light



SL.No.	Model No.	Power (Watt)	Lumen(LM)	CRI.	Color Temp (CCT).	Beam Angle	N.W(KG)	Materials	Power Factor (PF)	Dimention mm	LED Type
01	EL-ARHM-300	300W	495,00lm	>70Ra	2500K to 5500K	120°	7.5	Al+PC	>0.95	540x 370x175	3030
02	EL-ARHM-400	400W	260,00lm	>70Ra	2500K to 5500K	120°	7.9	Al+PC	>0.95	619x410x175	3030
03	EL-ARHM-600	600W	960,0lm	>70Ra	2500K to 5500K	120°	12.5	Al+PC	>0.95	713x410x180	3030
04	EL-ARHM-800	800W	1280,00lm	>70Ra	2500K to 5500K	120°	17.5	Al+PC	>0.95	910x420x180	3030
05	EL-ARHM-960	960W	1536,00lm	>70Ra	2500K to 5500K	120°	20.3	Al+PC	>0.95	1004x420x180	3030
06	EL-ARHM-1200	1200W	1920,00lm	>70Ra	2500K to 5500K	120°	25.7	Al+PC	>0.95	1192x420x180	3030

Features:

- System Light Efficacy 160-165 LPW
- Ultra Bright, Up to 192,000Lm
- Lumen Maintenance: L70>150,000 Hours (Calculated Using Tm-21 Calculator)
- Flexible, Modular Design & Multiple Choice of Optical Lenses & Easy Installation & Maintenance
- Input Voltage 100-277 VAC (347/480 VAC Optional) Dimming Optional
- IP65 & IK10 rated for all outdoor conditions
- 5 Years warranty
- Operating & Storing Temperature: -30 to 50°C (-22 to 131°F) & -40 to 80°C (-40 to 176°F)

