

LED Canopy Light



SL.No.	Model No.	Power (Watt)	Lumen(LM)	CRI.	Color Temp (CCT).	Beam Angle	N.W(KG)	Materials	Power Factor (PF)	Dimention mm	LED Type
01	OE-ARCL-80	80W	122,00lm	≥70Ra	2500K to 6500K	120°	2.1	Alumn.	>0.95	280×280×96.5	2835
02	OE-ARCL-100	100W	150,00lm	≥70Ra	2500K to 6500K	120°	2.1	Alumn.	>0.95	280×280×96.5	2835
03	OE-ARCL-120	120W	180,00lm	≥70Ra	2500K to 6500K	120°	3.1	Alumn.	>0.95	382×382×117.5	2835
04	OE-ARCL-150	150W	225,00lm	≥70Ra	2500K to 6500K	120°	3.1	Alumn.	>0.95	382×382×117.5	2835

Features:

- System Light Efficacy 150 LPW
- Easy Installation & Maintenance
- Lumen Maintenance: L70>100,000 hours (Calculated Using TM-21 Calculator)
- Input Voltage 100-277
- IP66 rated for all outdoor conditions
- 5 Years warranty
- Operating Temperature: -30 to 50°C (-22 to 131°F)
- Storing Temperature: -40 to 80°C (-40 to 176°F)
- Certifications; CE, RoHS,CB, ETL, DLC Pending

